

# DYNAPAC SMALL ASPHALT TANDEM ROLLERS

DYNAPAC CC1100 VI / CC1100C VI  
CC1200 VI / CC1200C VI  
CC1300 VI / CC1300C VI  
CC1400 VI / CC1400C VI



The sixth generation of the Dynapac CC1100/CC1200/CC1300/CC1400 VI small asphalt rollers are designed to meet the construction industry's tough conditions with the operator in mind, resulting in a robust, comfortable and modern machine for best compaction result. The new machine has a unique design with its' cross-mounted engine in combination with an excellent visibility and massive casted forks with flexible lifting/towing/tie down possibilities.



### Visibility

- Optimal visibility over the drums
- Efficient LED-lights for night-work
- Sliding seat possibilities



### Performance

- High vibration frequency
- Dual frequency
- Dual amplitude (CC1300 VI and CC1400 VI option)
- High efficient eccentrics
- Offset drums
- Powerful Kubota engine
- Edge press wheel/ cutting disc
- Chipsreader
- Asphalt temperature meter



### Ergonomics

- Low noise
- Easy to understand instrument panel
- Comfortable vibration damped operator platform
- Driver lever following the sliding seat
- Canopy roof for sun and rain protection



### Sprinkler system

- Pressurized sprinkler system
- Large water-tank
- 3 filtration system
- Sprinkler timer



### Transportation

- Foldable ROPS
- Flexible lifting/towing/tie down possibilities in the forks
- Central lifting point
- Optimized machine length for efficient transportation



### Serviceability

- Easy accessible daily service-points
- Reliable sprinkler system
- Cross-mounted engine for best access
- Dyn@Link remote monitoring



*Experience is the base of excellence. Dynapac will always help you to reach perfection.*



## APPLICATION



### EXCELLENT VISIBILITY

By moving the water tank to the rear part of the machine, we have managed to develop a machine with a unique design with a cross-mounted engine in combination with excellent visibility over the drums. The optional sliding seat of 8.3 in in combination with the improved engine hood design gives the operator the best sliding possibilities and visibility on the market. The optional ROPS-mounted LED working lights provide additional visibility.

### HIGH QUALITY COMPACTION

All rollers include efficient eccentrics guaranteeing optimum powerful performance in the vibration start-up process. The rollers feature high frequency compaction with the possibility to choose between dual frequencies depending on different conditions and applications. Dual amplitudes, for even more flexibility in different applications, are available as an option for CC1300 VI/CC1400 VI. A mechanical adjustable off-set function is a standard feature. By adjusting the rear frame to the left you will get an off-set of the front drum up to 2 in. Off-setting the drum makes it easier to compact close to walls and curbs with less risk of damaging the machine. The big drum diameter makes sure the asphalt is not shovelling in front of the drum creating transversal cracks. An optional front right mounted edge presser/edge cutter is available as well as an optional rear mounted chip spreader. For CC1300 VI and CC1400 VI a double front installation of edge presser/cutter is also available.

### COMFORTABLE WORKING ENVIRONMENT

The new roller is designed with the operator in mind resulting in a comfortable and modern driver's environment. The spacious and vibration damped operator platform enables great operator comfort even during long working days, thereby maintain the quality of the performance of the job done. A new comfort seat is available with weight adjustments and optional seat-heating. The forward and reverse lever is following the optional sliding seat for even better ergonomics and better control. An optional dual forward and reverse lever enables even better ergonomics and control of the compaction process. The modern instrument panel with keypad buttons and a display showing the most important functions facilitate the driver to operate the roller with precision. A small storage box under the seat, a cup/can holder and a 12v outlet on the operator platform are details adding extra comfort. An optional canopy protecting the driver from different weather conditions facilitate operator's comfort and efficiency. The canopy is foldable for easy transportation.

### RELIABLE WATER SYSTEM

The design of the pressurized sprinkler system facilitates a smooth and reliable compaction with maximum uptime. The rollers are equipped with a sprinkler system with an easy-accessible sprinkler pump and filter and sprinkler bars with 3 sprinkler nozzles on each drum. Automatic Water Control is standard on all machines. A 3-stage filtration system ensures clean water and prevents clogged sprinkler nozzles. The sprinkler timer helps the operator in saving water by adjusting the sprinkler intervals which means reduced downtime for water-refilling. The water tank includes as much as 54 gal for CC1100 VI / CC1200 VI and 79 gal for CC1300 VI / CC1400 VI. All of these features result in a minimal down-time for the operator.

1. FIRST CLASS VISIBILITY
2. HIGH QUALITY COMPACTION
3. COMFORT IN FOCUS
4. RELIABLE WATER SYSTEM
5. ENGINES FOR THE WORLDWIDE MARKETS
6. OPTIMIZED FOR TRANSPORTATION
7. CONTRIBUTION TO GREAT SERVICEABILITY
8. SAFETY FIRST



### **ENGINE ALTERNATIVES FOR THE WORLD MARKET**

Having sustainability and working environment in mind under the developing process resulted in the latest emission reduction technology to fulfill the worldwide emission regulations. The range is powered by durable, fuel-efficient Kubota diesel engines which reach unbeatable performance with maximum up-time. We offer engine alternatives which meets the engine emission regulations worldwide. For CC1100 VI and CC1200 VI for North American markets we offer a 37,5 hp T4/V Kubota engine with a DPF after-treatment system alternatively a somewhat lower horse-powered 25 hp engine fulfilling the T4/V emission legislations without the cost and complexity of an after-treatment system. For markets not yet having the T4/V emission legislation requirements or the ultra-low sulfur fuel we offer a stage IIIA 35 hp engine alternative. For the CC1300 VI / CC1400 VI we have one T4 engine alternative at 50 hp for the North American market. A IIIA alternative at 48 hp is also available

### **OPTIMIZED FOR TRANSPORTATION**

Fast and easy transportation between jobsites increases the operator's efficiency. The design work has resulted in a machine well suited for optimized transportation. Flexible lifting/towing/tie down possibilities built in the robust casted forks enabling fast and easy transportation. An optional central lifting point for CC1100 VI and CC1200 VI makes the transportation between jobsites easier. The foldable ROPS is easy to fold. The total machine length including the ROPS is 94.5 in for CC1100 VI/1200 VI meaning the machines can be cross-loaded on a truck enabling twice as many rollers fitted on the truck. The total machine length for CC1300 VI/1400 VI is 112 in.

### **GREAT SERVICEABILITY**

The design of the rollers contribute to great serviceability. The engine hood is large and possible to fully open for best accessibility. The engine is cross-mounted for optimal serviceability. The major daily service-points under the hood are on one side. Sprinkler nozzles, water-pump and filter for the sprinkler system are easy to reach, the water pump and filter are easy accessible behind a cover above the rear drum.

### **BUILT-IN SAFETY**

Interlock is a standard feature on all rollers ensuring no accidental starting. Failsafe brakes automatically engage when needed. The separate parking brake switch on the instrument panel helps prevent accidental activating. The machine has a lowered operator platform making it easy to climb up on the machine. An ergonomic foot-step and sturdy handgrips makes the machine easy to climb on to.

## TECHNICAL FEATURES AND BENEFITS DURING COMPACTION

- 1** **VISIBILITY**  
*The robust engine hood is designed for optimal view over the front drum. In combination with the optional sliding seat of totally 8.3 in it gives the operator the best sliding possibilities and visibility on the market.*
- 2** **MODERN INSTRUMENT PANEL**  
*A modern instrument panel with keypad buttons and a display showing the most important functions facilitate the driver to operate the roller in a controlled way.*
- 3** **OFFSET**  
*A mechanical adjustable offset function is available on all models. By adjusting the front frame to the right you will get an offset of the front drum up to 2 in making it easier to compact close to walls and curbs with less risk of damages of the machine. Also it increases the surface capacity and gets rid of marks in the mat when making the last pass.*
- 4** **SPRINKLER SYSTEM**  
*The design of the pressurized sprinkler system facilitates a smooth and reliable compaction with maximum uptime. The rollers are equipped with a sprinkler system with easy accessible sprinkler pump and filter and sprinkler bars including 3 sprinkler nozzles on each drum.*
- 5** **EFFICIENT ECCENTRICS**  
*The rollers include efficient eccentrics guaranteeing optimum powerful performance in the vibration start-up process.*
- 6** **WATER CAPACITY**  
*The large water tank includes a capacity of 54 gal for the CC1100 VI/1200 VI and 79 gal for the CC1300 VI/1400 VI. In combination with the sprinkler timer, it helps the operator to save water which means less downtime for water-filling.*
- 7** **NIGHT-LIGHTS**  
*Optional ROPS-mounted working LED lights provide additional visibility during night-work.*
- 8** **CANOPY**  
*An optional canopy protecting the driver from sun and different weather conditions facilitates operator's efficiency. The canopy is foldable for easy and efficient transportation.*
- 9** **OPERATOR EFFICIENCY & COMFORT**  
*The forward and reverse lever follows the sliding seat for best ergonomics. The sliding seat possibility and an optional lever facilitates even better ergonomics and control of the compaction process.*
- 10** **ENGINE ALTERNATIVES**  
*Powerful and fuel efficient IIIA/T4/V Kubota engine alternatives for the worldwide emission regulations.*
- 11** **SERVICEABILITY**  
*A cross-mounted engine and a possibility to fully open engine hood enable easy accessible daily service-points. Sprinkler pump and filter easy accessible behind a cover above the rear drum.*
- 12** **OPTIONAL EDGE PRESSER/CUTTER**  
*Edge presser tool for better joint binding. Front right mounted for CC1100 VI/1200 VI plus a double front mounted alternative for the CC1300 VI/1400 VI and a cutting disc of 2 in cutting depth is available as option.*
- 13** **CHIP SPREADER**  
*Optional rear mounted chip spreader. Which is to be used for creating friction on newly laid asphalt.*
- 14** **TRANSPORTATION**  
*Flexible lifting/tie down/towing possibilities in the casted forks enabling fast and easy transportation. An optional central lifting point makes transportation between job-sites easier.*
- 15** **OPERATOR'S COMFORT**  
*A small storage box under the seat, a cup/can holder and a 12 v outlet on operator's platform contributes to driver's comfort.*
- 16** **ENGINE HOOD**  
*The robust engine hood is made in an impact resistant material with great durability.*





4

12

5

1

3

10

11

16

2

15

7

9

6

14

13

1. MACHINE TYPES ▶



Standard drums



Combi with wide base tires

2. ROPS or no-ROPS ▶



3. ENGINES ▶



**CC1100 VI and CC1200 VI**

Kubota D1703-DI (T4/V) 25 hp

Kubota D1803-CR (T4/V) 37.5 hp

**CC1300 VI and CC1400 VI**

Kubota V2403-CR E4B (T4) 50 hp

**CONNECTING TO THE FUTURE**

With the Dyn@Link system, Dynapac offers a tool which is an excellent way to monitor your roller. Dyn@Link Provides information about your rollers positioning, engine hours and geo-fencing. Thanks to the online portal and the Dyn@Link app, users can get access to this information from anywhere, at any time.



#### 4. FORWARD/REVERSE LEVER ▶

Dual Forward/Reverse lever  
standard for North America



#### 5. STANDARD EQUIPMENT ▶

- Air clean indicator
- AVC
- AWC
- Back up alarm
- Battery disconnecter
- Comfort seat
- Dual forward/reverse lever
- Dual frequency
- Emergency stop
- Filters for sprinkler system (3)
- Fuel level display
- Horn
- Hour meter
- Hydraulic checkpoints
- Ignition key
- Interlock
- Lights, working
- Lights, working 1 extra rear
- Lights, warning
- Lifting / towing / tiedown eyelets
- Lockable instrument panel
- Offset
- Operator's platform vibration damped
- Pressurized sprinkler system
- Rear view mirror
- ROPS foldable
- Rotating beacon
- Seat belt 3"  
(available for machines with ROPS)
- Spring loaded scrapers
- Steering wheel
- Vibration shut off,  
individual front & rear
- 12-volt outlet on platform

#### 6. OPTIONS

- Asphalt temperature meter  
(CC1300 VI/1400 VI only)
- Biodegradable hydraulic oil
- Brake release tool
- Can holder
- Canopy
- Central lifting point (CC1100VI/CC1200VI only)
- Certificate, CE
- Chip spreader
- Comfort seat with seat-heating
- Customized colours (one or two colours)
- Decal, risk location (GOST)
- Dual amplitude (CC1300VI/CC1400 VI only)
- Dyn@Link
- Edge presser-dual front mounted  
(CC1300VI/CC1400 VI only)
- Edge presser-front/right mounted
- Edge cutter disc, 50mm
- Extra set of manuals
- Fire extinguisher
- First aid kit
- Flow divider (not combi)
- Hearing protectors
- Lights, driving: Left or Right incl.  
direction lights
- Lights, direction- mounted on both sides of  
the hood
- Lights, license plate
- Lights, working ROPS mounted LED
- Rotating beacon (ignition controlled)
- Service kit 50/500/1000h
- Slow Moving Vehicle sign (SMV)
- Tool set
- Water tank cover (lockable)



## ***COST CONTROL THAT SAVES BIG***

Being active in the Road Construction business requires considerable investment. Every square meter involves an operational cost comprised of fixed costs such as interest on equipment acquired, labor costs, insurance and equipment depreciation, but also variable costs such as expenses for fuel, wear and maintenance.



### **Wear cost**

Since Dynapac always uses high-quality wear parts, the time that is needed to change them can be kept to a minimum.

Customers who use original Dynapac spare parts will improve reliability and protect their investment.

### **Operator cost**

The operator is always a very big part of the total cost. Operators using Dynapac equipment will maximize their efficiency with great ergonomics and easy-to-operate equipment.

### **Investment cost**

The purchase price is often a relatively small part of the total cost. Dynapac rollers and pavers maintain their high value throughout their working life thus holding a good value if you want to sell it in the future.

### **Maintenance cost**

All road construction equipment need regular check-ups such as change of oils and filters. Dynapac always strives to use components that require as little maintenance as possible.

### **Fuel cost**

Fuel expenses make up a large part of your total cost. Since Dynapac rollers and pavers are equipped with a very efficient hydraulic system, your fuel cost will be kept at a low level.

## SERVICE COMMITTED TO YOUR FUTURE

### WHAT?

#### GENUINE PARTS AND KITS

- Preventive maintenance kits
- Genuine Filters
- Fluids and lubricants
- Wear and repair kits
- Upgrade Kits

#### SERVICE

- Right competence
- Training program
- Inspection & service program
- Extended Warranty & Service Agreement

#### CONSUMABLES

- Road Milling  
Tools (bits)

### HOW?

#### GLOBAL DISTRIBUTION NETWORK

- Always close to you

#### DYNAPAC.COM

- Kit selector
- Fluid selector
- Shop Online

#### DYN@LINK

- Manage your fleet
- Timely interventions planned with service alerts

## PREVENT THE COST OF A BREAKDOWN

### REGULAR MAINTENANCE PREVENTS COSTLY STANDSTILLS.

Equipment break-downs have a direct impact on your productivity. No production means revenue loss, but the fixed costs stay the same, resulting in lower profitability. By avoiding break-downs and increasing the reliability of your machine, you will be able to maximize your productivity which will immediately improve your profitability.

## PREVENTIVE MAINTENANCE KITS

### PREVENTIVE MAINTENANCE KITS

All-in-one box that is tailored to match your equipment. Easy to obtain and attractively priced, our preventative maintenance kits contain all the parts required for your equipment's scheduled maintenance program. When installed by one of our certified technicians, you keep equipment downtime to a minimum and its uptime to a maximum throughout its working life.

### PREVENTIVE MAINTENANCE PAYS BACK

Equipment needs preventive maintenance that demands

- Timely intervention to avoid expensive breakdowns and maintain a higher residual value



**Lower Cost of Ownership**  
Maintenance prevents more costly repairs



**Increased equipment reliability**  
Full equipment uptime



**Higher resale value**

## DYNAPAC SMALL ASPHALT TANDEM ROLLERS

	CC1100 VI	CC1100C VI	CC1200 VI	CC1200C VI	CC1300 VI	CC1300C VI	CC1400 VI	CC1400C VI
<b>DRUM</b>								
Drum width, in	42	42	47	47	51	51	54	54
<b>MASSES</b>								
Operating mass, lbs (incl. ROPS)	5 292	4 900	5 733	5 100	8 600	8 150	9 480	8 600
<b>TRACTION</b>								
Speed range, mph	0 -6	0 -6	0-6	0-6	0-6	0-6	0-6	0-6
Vertical oscillation	±10°	±10°	±10°	±10°	±10°	±10°	±10°	±10°
Theor. gradeability	46 %	71 %	42 %	65 %	42%	41%	37%	39%
<b>COMPACTION</b>								
Centrifugal force, lb high/low frequency D1703	6520 / 5620 6295 / 5620	6520 / 5620 6295 / 5620	7650 / 6520 7420 / 6520	7650 / 6520 7420 / 6520	8550/6980	8550/6980	9680/7880	9680/7880
Centrifugal force for dual amplitude versions T4 and Stage V only, lb					8550/4725	8550/4725	9680/4950	9680/4950
Nominal single amplitude, in	0,02	0,02	0,02	0,02	0,02	0,02	0,02	0,02
Nominal dual amplitude, in					0,02/0,008	0,02/0,008	0,02/0,008	0,02/0,008
Static linear load lbs/in (front/rear)	60 / 66	60	58 / 64	58	80 / 88	80	85 / 90	85
Vibration frequency, VPM high/low D1703 D1803 V2403 T4 single amplitude V2403 T4, dual amplitude	3960/3660 3900/3660	3960/3660 3900/3660	3960/3660 3900/3660	3960/3660 3900/3660		3240/2940 3240/3660	3240/2940 3240/3660	3240/2940 3240/3660
<b>ENGINES</b>								
<b>CC1100 VI and CC1200 VI</b> Kubota D1703-DI (T4/V) 25 hp Kubota D1803-CR (T4/V) 37.5 hp <b>CC1300 VI and CC1400 VI</b> Kubota V2403-CR E4B (T4) 50 hp								
Water tank, gal	54	49+5	54	49+5	79	79+7	79	79+7

PMI 3492100193 January 2021

Your Partner on the Road Ahead



Dynapac North America LLC  
 342 Patricia Lane, Suite 104, Fort Mill, SC 29708  
 Phone: (800) 651-0033 - Fax: (803) 753-9612  
[www.dynapac.us](http://www.dynapac.us)