LG500: electric start, plate 750mm

3382 0000 56



Create PDF sheet

Request information

Atlas Copco Construction Equipment 800 732 6762

Send an email

QUICK LINKS

Atlas Copco Print Shop Atlas Copco Photo Archive

Product information

Photos & Video

High speed and world-class compaction efficiency make our forward and reversible plates excellent for compacting medium to deep layers of granular soils. The high speed, balanced design and hydraulic control system contributes to easy, precise handling on the roughest of surfaces or for spot compaction.

Features & benefits

Hydraulic forward/reverse lever

Engines with low fuel consumption and emissions

Heavy-duty protection frame and impact resistant steel covers protect engine and transmission.

High quality bottom plate

Applications

Cobbles and boulders

Sand and Gravel

Silt

Technical data

Units:

:	Metric	Imperi

	onio. Inerio	
Technical Specifications		
Operating mass	1157 lb	
Centrifugal force	-	
Plate width	29 1/2 inch	
Engine brand	Hatz	
Power	8.2 kW	
Speed	-	
Amplitude	1/16 inch	
Frequency	60 Hz	
Sound power level guaranteed	109 dB(A)	
Sound pressure level at operators ear	91 dB(A)	
Vibration emission value	2.1 m/s²	

Product views







