





Shown with gasoline engine



Ergonomic Operator Safety Station With Safety Screen



Heavy duty log advance chain and engine guard

Outstanding Features

The Multitek Pro Model 1610 EZ Firewood Processor has many features that are well suited for the growing firewood producer. This machine features a 2-strand hydraulic folding live deck for processing logs up to 12 ft (3.65 m). This industry workhorse is professionally designed for maximum performance and low maintenance. With a 5.5 second cycle time, this machine will efficiently cut and split your hardwood logs into saleable firewood. The economical patented bent axis chainsaw mechanism is 35% faster than comparable bar & chain machines and significantly less maintenance. The 1610 EZ is professionally engineered to be the most efficient, safest, and operator friendly entry machine available today. The 1610 EZ is manufactured on the identical basic mainframe assembly as our larger 16 series machines! This is a machine designed to work and made to last!

The Most Economical Entry Level Firewood Processor Available

Increase production and reduce labor costs with the economical 1610EZ. The machine features an ultra fast load sensing saw mechanism that easily handles the hardest of logs and cuts them up quick. With gas, diesel, PTO, and 3-phase electric models available this machine is very easy on fuel and electricity. The gas and diesel engine option machines consume approximately 1.1 gallons (4.1 L) of fuel per operating hour under full load.

Operator Ergonomics & Safety

The operator of the machine is behind a safety shield allowing clear visibility of the complete process. The machine is operated with two four-way joysticks that handle the operating functions of the machine, making it very simple to operate while wearing gloves and other recommended safety gear. For our European Union customers, the 1610 EZ is available with the CE Mark to comply with safety measures set forth by the European Economic Area. The 1610 EZ is one of the safest firewood processors available in the world.

High Performance Guaranteed

The 1610 EZ is designed to process 1 to 2 cords of cut & split firewood per hour. The machine is set up efficiently to allow for the operator to advance your next log and clamp it while the machine is splitting, decreasing cycle time and increase production time. The 2-strand hydraulic powered log deck is rugged built and has custom log flippers allowing only one log into the log infeed trough at one time. Optional equipment for the 1610 EZ includes: CE MARK, Electric Stationary Configuration, Ergonomic Operator Station with Seat, Extended Log Decks, 4, 6, or 8-way Hydraulically Adjustable Wedges, and Optional Integral 15' (4.57 m) or Separate 20' (6.1m) or 30' (9.1m) outfeed conveyors.

1610EZ







Shown with full log deck



Easy to use operator 4 way joysticks

Your Multitek Dealer:

Manufactured by:



375 Progress Street Prentice WI 54556 U.S.A. 715-428-2000 / Fax 715-428-2700

Toll Free: 800-243-5438 www.multitekinc.com

E-Mail Address: sales@multitekinc.com

Multitek reserves the right to change or improve products without notice and the right to change prices or discounts without notice.

MULTITEK products are covered by several U.S. & Canadian Patents.

Multitek Product Warranty - 12 months.

Printed in U.S.A. 3M 6/10

FIREWOOD PROCESSOR MODEL 1620 SS

PERFORMANCE:

- Production Rating 1.0 2.0 Full Cords Per Hour
- Splitter Cycle Time 5.5 Seconds
- Maximum Log Length 12' (3.65 m)

 Maximum Log Diameter 18" (45.72 cm)
- Minimum Log Diameter 3" (7.62 cm)
- 24" (61 cm) Split Chamber
- 20 Tons of Splitting Force

SPECIFICATIONS:

- Engine Options: 25 hp (18 kw) -34 hp (25 kw) Subaru or Kohler gasoline
- Engine Options: 25 hp (18 kw) -34 hp (25 kw) Kubota or Yanmar diesel
- PTO or 3-phase electric power
- Transport Length: 21' (6.3 m)
 Towing Width 7'5" (2.28 m)
 Weight 3,200 lbs (1,451 kg)
- 2" Tow Ball or Euro Tow Ring
- **Electric Brakes**
- 1 Year Warranty
- 10 or 20 Gallon Steel Fuel Reservoir
- 45 Gallon Steel Hydraulic Tank with In-Tank Filter

PROCESSOR OPTIONS:

- Integral 15' (4.57 m) Vulcanized Belt Conveyor
- Separate 20' (6.09 m), 30' (9.14 m), 35' (10.66 m) conveyors
- 3-phase electric power
- Extended live deck
- Night Light Kit
- Stationary nonpowered log deck
- **CE MARK for European Union**

