



MULTITEK[®] MODEL 2020CSC

FIREWOOD PROCESSOR

The *NEXT GENERATION* of high volume professional processors with *INTEGRATED STACKING CONVEYOR*.

The Multitek Model 2020CSC is the first professional firewood processor to be manufactured with a pintle hitch hookup and with an integrated stacking conveyor. Only one person is required to operate and relocate this firewood processor. It can efficiently and accurately process low grade hardwood logs up to 20" (51 cm) in diameter by 20' (6.1 m) in length at a rate of up to 2.0 cords per hour, 128 cubic feet per cord (3.62 cubic meters).

Designed for contract firewood processing, making windrows piles of firewood or to produce more revenue as a rental machine.

FEATURES INCLUDE:

- Joystick style operator controls
- Very low operating cost
- Reinforced V shape style infeed log trough
- Multitek exclusive infeed shuttle grapple
- Interchangeable 4, 6 or 8 way wedges

- ONE MAN OPERATION
- FULLY PORTABLE
- PROVEN DEPENDABILITY

Shown with optional operator cab.



Over a quarter of a century of industry leadership in production, reliability, lowest downtime and maintenance cost.

2020CSC PERFORMANCE:

Production Rating: Approximately 1.5 - 2.0 Cords Per Hour (rated in "98917full cord" based on 128 cubic feet (3.62 m³) volume per cord).

- Maximum Log Length: 25' (7.62 m)
- Minimum Log Length for Deck: 8' (2.4 m)
- Maximum Log Diameter: 20" (51 cm)
- Minimum Log Diameter: 3" (7.6 cm)
- Splitter Cycle Time: 4 second round trip
- Feed System: Shuttle Grapple
- Saw Chain .404 (18h, 80 ga. saw bar)
- Splitter Opening: 27" (68 cm)
- Wedges - Adjustable Floating 4, 6 or 8
- Conveyor Discharge: 9'9" (2.98 m)

SPECIFICATIONS:

- Engine: John Deere Diesel /turbo
- Horsepower: 66hp (41 kw) Liquid Cooled
- Diesel Fuel Capacity: 50 gal. (189 L)
- Fuel Consumption: 1.5 gph (5.7 LPH)
- Hyd Reservoir Capacity: 70 gal. (265 L)
- Hydraulic Oil Cooler: Standard
- Bar Oil Capacity: 2.4 gal. (9.5 L)
- Trailer Hitch Type: Pintle
- Tire Size: P235/80R16
- Trailer Suspension: Leaf Spring
- Transport Length: 38' 2" (11.62 m)
- Transport Width: 8'6" (2.59 m)
- Transport Height: 11'1" (3.37 m)
- Operating Width: 13'7" (4.14 m)
- Axles: Tandem w/elec brakes - ICC Std Lights
- Log Trough Length: 13' (3.96 m)
- Livedeck Load Height: 5'4" (1.62 m)
- Tongue Weight: 1,290 lb. (588 kg)
- Weight: 12,330 lb. (5,626 kg)

OPTIONS:

- Operator Cab Enclosure, Heated
- Cab Air-conditioning
- Short Log Live Deck Arm
- Log Deck Extension
- 4 Way Interchangeable Wedge
- 8 Way Interchangeable Wedge
- 11H Cut-Off Saw Chain
- Anti-Vandalism Package
- Floodlights

Powered with a 54hp (41kw) turbo-charged Series 220 John Deere liquid cooled diesel engine with a standard two year engine warranty and a 50 gallon diesel fuel capacity.



The Model 2020CSC is a highly mobile machine with tandem axles, single tires, electric brakes and a pintle hitch for towing.



PO Box 170
Prentice WI 54556-0170 USA
800-243-5438

*To view our complete product line
or a dealer near you, visit our website at:*

www.multitekinc.com

E-Mail Address: sales@multitekinc.com

Distributed by:

**Tough, reliable and easy to use
Rugged machines for the labor intensive, backbreaking business.**