



FEED SYSTEM: (HYDRAULIC)

Recycling Equipment Precision/Husky Dealers Parts Inventory Shipping

Used Equipment For Sale

Contacts

Contact Us!

GENERAL SPECIFICATIONS

FEED RATE: (3-KNIFE CHIPPER)

3/4" [19mm]Chip:

7/8" [22mm] Chip:

1" [25mm] Chip:

101 ft. / [30.8m] / min.

118 ft. [35.9m] / min.

135 ft. [41.2m] / min.

Top roll length: Height: 48" [1220mm] 13'-2" [4m] Bottom roll diameter: Width: 11'-6" [3.5m] 21" [533mm] Top roll diameter: Length: 35'-0" [10.7m] 21" [533mm] Spout roll length: 46" [1168mm] Weight: 67,260 lbs. [30,573kg] Bottom roll length: Suspension: 46" [1168mm] 3-Axle Springs Spout roll diameter: Spout Opening: 23" x 48" [584mm x 1220mm] 21" [533mm]

POWER OPTIONS:

Caterpillar/Cummins 600HP [339kw] and up.

STANDARD EQUIPMENT:

- 66" [1676mm] 3-knife Precision Chipper, LH
- Husky XL-175 Knuckle Boom Loader
- 300gl [1136 L] Hydraulic Tank135gl [625 L] Fuel Tank
- Complete Engine and Gauge Panel in Cab with Engine Start-Up and Shut-Down Switches
- Fully Steerable End Discharge Pipe Hydraulically Controlled from Operators Cab
- Wichita Model ATD-224, Air

- One (1) 12CFM Air Compressor, 10HP [7.5kw] Gasoline Powered, for Changing Knives and Maintenance
- 3-Axle Spring Suspension with Steel 70R255/22.5 Steel Belted Radial Tires
- Operators Cab with Sliding Window and Door, Hydraulically Tilts for Transport
- All Bearings are Heavy-Duty, Double Row Tapered Roller Bearings



- Clutch Mounted on Chipper Sheave
- One (1) 12CFM [339lpm] Air Compressor on Main Diesel Operates Air Clutch
- Pneumatic Air Wrench
- Hydraulically Powered Stabilizers, Discharge Spout, Feed Rolls and Hood
- 150 Micron Suction Filters and Quad Return Filters.
- Fire Extinguisher, 25gl [95L] Refillable

Return to Timber Harvesting Equipment

Privacy Policy | Site Hosted by VentureNet | Email: sales@precisionhusky.com



Copyright © 2004, Precision Husky Corporation, All Rights Reserved. | Site Design by RP Design