

TIMBERPRO



- 40° Lateral Tilt Adapter (Optional 360°)
- Constructed from Grade 100 Material
- 6500 lbs (with 40-deg tilt adapter)
- 22" plus (56 cm) Cutting Capacity
- 4.0 sqft Accumulation Area
- Quadtooth® Bolt-on Holders

TDS-22

Specifications

- ▶ 40° Lateral Tilt Adapter (Standard)
- ▶ 360° Rotate (Optional)
- ▶ Frame Constructed from Grade 100 Material
- ▶ 3/4" T1 Grade Butt Plate
- ▶ Quadtooth® Bolt-on Holders
- ▶ 22" plus (56 cm) Cutting Capacity



Operating Weight

(with 40-deg rotator)	6500 lbs (2,948 kg)
(with 360-deg rotator)	7400 lbs (3,357 kg)

Dimensions

Height	92"
Width	55"
Depth	62"
Max Throat Opening	30"

Accumulation Area	4.0 sq ft
--------------------------	-----------

Saw Information

Tip to Tip diameter	52"
Saw RPM	1,150
Number of Teeth	20
Saw Kerf	2"

TimberPro Inc reserves the right to change specifications without notice or obligation. Product Illustrations may be equipped with non-standard equipment.

TIMBERPRO
1407 Industrial Dr.
Shawano WI 54166 USA
www.timberpro.com