



TERRAMAC RT15R RUBBER TRACK CARRIER

Standard RT15R Specs

The Terramac RT15R is redefining jobsite efficiency with its low ground pressure, 360-degree upper frame rotation and 30,000 lb. carrying capacity. Operators can dump payloads at any angle without repositioning the machine, reducing cycle times and track wear. Maximize your crew's productivity in the most challenging environments.

DIMENSIONS

Full Length	20' 4"
Full Height	10' 11"
Width Over Tracks	10'
Min Ground Clearance	23"
Front Overhang	2' 8"
Track Gauge (Center-to-Center)	7' 5"
Track Width	2' 8"
Undercarriage Length (Idler to Drive Hub)	12' 3"
Dump Bed Loading Height Over Side	7' 3"
Height of Rock Bed Side (Vessel)	21"
Length of Rock Bed (Vessel)	10' 11"
Width of Rock Bed (Vessel)	9' 6"
Dumping Angle	60°
Machine Weight (with bed)	40,410 lbs.

ENGINE

Manufacturer	Cummins
Model	B6.7 Performance Series Stage V/T4F
Displacement	543 cu. in.
Horsepower	318 HP @ 1800 RPM
Electrical System	12 VDC
Battery	(2) 12V GRP 31,100 CCA each
Fuel Capacity	86 gallons



HYDRAULICS

Transmission	HST
Drive Pump Max Flow (x2)	64 gpm / side
Drive Pump Max Pressure	6,090 PSI
Tandem Gear Pump Max Flow	
Front Section (Aux Output)	19.7 gpm @ 3045 PSI
Rear Section (HST Drive)	24.5 gpm @ 2825 PSI

PERFORMANCE

Max. Carrying Capacity	30,000 lbs.
Travel Speed - 1st Gear	3.6 mph
Travel Speed - 2nd Gear	6.9 mph
Gradability	58% (30°)
Turning Radius	Zero Turn
Ground Pressure (loaded)	8.13 PSI
Ground Pressure (unloaded)	4.77 PSI

T2615R1

TERRAMAC RT15R RUBBER TRACK CARRIER

Standard RT15R Units & Dimensions

